



China Im8uu Bearing Supplier



6000 Bearing 2D drawings and 3D CAD models

NTN NSK Koyo NACHI Deep Groove Ball Bearings 6000 6100 6200 6300 6800 6900

Bearing No. 6000

Size	10x26x8 mm
Bore Diameter	10 mm
Outer Diameter	26 mm
Width	8 mm
d	10 mm
D	26 mm
B	8 mm
C	8 mm
r min.	0.3 mm
da min.	12 mm
Da max.	24 mm
ra max.	0.3 mm
Weight	0.019 Kg
Basic dynamic load rating (C)	4,55 kN
Basic static load rating (C0)	1,97 kN
(Grease) Lubrication Speed	30000 r/min
Enclosure	Open
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	10 mm
Outside Diameter	26 mm
Width	8 mm
Fillet Radius/Chamfer	0.3 mm
Dynamic Load Rating	4,550 N
Static Load Rating	1,970 N



China Im8uu Bearing Supplier

Limiting Speed - Grease	30,000 rpm
Limiting Speed - Oil	36,000 rpm
Factor f_0	12.4
Radial Clearance	0.002 to 0.013 mm
d_a (min)	12 mm
D_a (max)	24 mm
r_a (max)	0.3 mm